

Le premier IP PHONE (TOUT EN UN) / DIRTEL IP PHONE IP990
(DIAL-UP H.323 Modem + BROADBAND RJ45 Lan Phone + PSTN Line)

• Description de **IP990**



Nom du produit : IP PHONE IP990

Model Number : IP990 Brand Name : DIRTEL

Place of Origin : TAIWAN Price Terms : FOB FRANCE cf price
liste **Quality/Safety Certifications : CE, FCC**

Payment Terms : T/T in advance or **WESTERN UNION**

Minimum Order : 1 pièce pour échantillon = 249 EUROS et 50
pcs Minimum pour 165 EUROS/pcs **FOB FRANCE**

Delivery Lead Time : EN STOCK

Supply Ability : 60,000 units/month

Contact Information

Company Name : DIRTEL FRANCE

Contact Person : Mr Ayité d'ALMEIDA

Address :
DIRTEL FRANCE
5, rue Barye
75017 Paris
FRANCE
france@dirtel.net ou ip@dirtel.net

Zip: F-75017

E.mail: france@dirtel.net ou ip@dirtel.net

Mobile: +0033 625287411 ou +233 244 27 68 39

Fax: +33 (0)1 48 02 09 73

Web Site: <http://www.dirtel.net/IP990>

Features:

1) IP PHONE support (DIAL-UP + BROADBAND RJ45 + PSTN);

- Easy to use, simple to activate
- VAD (Voice Activity Detection)
- Volume control
- Speed dialing keys
- Phone book + Call log Fonctions
- Last number redial
- LCD display
- Call Mute
- Silence suppression
- Echo cancellation/compensation
- Excellent voice quality DSP technology
- Network management with SNMP-based NMS
- Software updates/upgrades via remote access
- Interoperable with standards-based gatekeepers and gateways
- Configurable phone number assignment to match dial plan
- Remote management via SNMP, Telnet and HTTP
- OEM customization available
- 1-year warranty

SPECIFICATIONS

LAN Interface

Standards : ITU H.323 v4, H.225, H.245
ITU G.711, G.723.1, G.729.A, IEEE 802.3
10/100 base-T

PPPoE, DHCP, Lan STATIC

Management : Telnet, RS-232, http

CODEC Options : G.711, G.729.A, G.723.1

Power : 5VDC, 2A

Dimensions : 14cm W × 4.3cm H × 17.5cm D

Weight : 0.73kg

Operating Temperature : 32° to 131° F (0° to 55° C)

Operating Humidity : 10% to 85% noncondensing

Storage Temperature 32° to 149° F (0° to 65°)

Storage Humidity : 5% to 90% noncondensing

Dial-up Interface

- Data Rates from 300 bps to 56k bps. (If needed in use, the rate can be limited by software)

- Data Modulation Standards V.90, V.34, V.432bis, V.22bis, V.22, V.23, V.21 and V.23 reversible (Minitel), Bell 212, Bell 103 Dialup Modem V.42

Error Control

- Country Code support

- V.42 Error Control

- V.42bis Compression
- Protected Against Surge and Over voltage on the Telephone Line Standard
- ITU H.323 v4, H.225, H.245
- ITU G.723.1

Codec

- G.723.1
- Call log fonctions : Received, Dialed, Missed calls, Tx/Rx calls

PSTN Fonctions

- RJ11 Normal telephone line plug in.
- Can be use like normal line phone
- Speacker phone
- redial, hands free support, speed dial, phonebook,.
- 132 x 32 pixel LCD display
- Powerful phone book, can save 100 phone number and contact information
- No need to dial area code when calling local number
- Dail type : tone + pulse
- Volume : Mic + speacker (- +)
- Color : milk white
- Integrated RS232 interface for PC communication.
- Phone Book
- Incoming call reminder if provide by PSTN Operator
- 3 speed dialing number
- Last call redial
- Flash Fonctions.
- Records history: auto saves the last 100 dialed/received phone numbers, and last 10 missed calls

Inner packing: box

Dimensions: 533 x 363 x 454mm

Outer packing: 10 units/carton

Dimensions: 72 x 320 x 250mm

Menu Structure

Call Log	Rcvd Calls		
	Dialed Calls		
	Tx/Rx Calls		
	Delete All		
Phone Book	Find Number	By Index	
		By Name	
	Add		
	Memory Dial	M1/ M2/ M3	
	* Delete All		
Ring/Volume	Ring Select	Ring 1	
		Ring 2	
		Ring 3	
	Volume		
Acct Balance			
* Setup	My Phone		
		* User PWD	
		* Admin PWD	
	Network	Auto Detect	NetDetect
			Start
			Cancel
	Mode Select	LAN(Static)	IP
			Subnet Mask
			Gateway
			DNS
		DHCP	
		PPPoE	PPPoE ID
			PPPoE PWD
	NAT	Enable	IP
			Subnet

		Mask
		Disable
Link Speed	LAN	
	PC	

Call Setup	Service	MAC Address
		GK Address
		H323ID
		On-net No
	TTL	

Modem	Time-out	
	Select Profile	ISP 1(Name)
		ISP 2(Name)
		ISP 3(Name)
	ISP 1(Name)	Name
	ISP 2(Name)	Tel No.
	ISP 3(Name)	ID
		PW

Time	Time Server
	Time Zone
	Summer Time

PSTN	Flash Time
	Dial Type
	County Code

Default

Information	Network
	Version
	Mac Address

Reboot